



info@morclean.com

www.morclean.com

Tel: 01246 471147

# Oilsafe

Designed For Where There Is A Risk Of Regular Contamination With Oil Or A Forseeable Risk Of Significant Spillages

Model	Area Drained (m2)	Diameter (mm)	Length inc Silt (mm)	Overall Height (mm)	Capacity (litres)		Access Dia (mm)	Options	
					Silt	Oil		Class 1	Class 2
OS167-1/2	167	1000	2400	1300	300	30	600	✓	✓
OS333-1/2	333	1530	2300	1830	600	60	600	✓	✓
OS556-1/2	556	1530	3300	1830	1000	100	600	✓	✓
OS833-1/2	833	1530	3600	1830	1500	150	600	✓	✓
OS1111-1/2	1111	1840	3900	2140	2000	200	600	✓	✓
OS1389-1/2	1389	1840	4649	2140	2500	250	600	✓	✓
OS1667-1/2	1667	1840	5398	2140	3000	300	600	✓	✓
OS2222-1/2	2222	1840	6758	2140	4000	400	600	✓	✓
OS2778-1/2	2778	1840	8849	2140	5000	500	2 x 600	✓	✓
OS3333-1/2	3333	1840	10476	2140	6000	600	2 x 600	✓	✓

Additional Items
Mains Alarm (Mandatory)
Solar Alarm
Access Shaft mtr
Replacement Filter
Replacement Filter Wrap

Stephenson Road, Speedwell Industrial Estate, Staveley, Chesterfield, Derbyshire S43 3JN