



info@morclean.com

www.morclean.com

Tel: 01246 471147

Streamflow

Designed For Contaminated Water Run Off
eg. Car Parks and Hard Standings

INCLUDING SILT									
Model	Area Drained (m2)	Diameter (mm)	Length Inc Silt (mm)	Overall Height (mm)	Capacity (litres)		Cover level to invert (mm)		Access Dia (mm)
					Silt	Oil	Inlet	Outlet	
SFS833	833	1000	1400	1750	150	22.5	625	675	600
SFS1670	1670	1000	1400	1850	300	45	725	775	600
SFS2500	2500	1000	2373	1850	450	67.5	725	775	600
SFS3340	3340	1000	2487	1850	600	90	725	775	600
SFS4440	4440	1220	2506	2245	800	120	900	950	600
SFS5550	5550	1220	2683	2245	1000	150	900	950	600
SFS6944	6944	1220	3333	2635	1250	188	710	760	600
SFS8330	8330	1840	2682	2635	1500	225	710	760	600
SFS11110	11110	1840	3094	2870	2000	300	945	995	600
SFS13888	13888	1840	4375	2870	2500	375	945	995	600
SFS16666	16666	1840	4571	2870	3000	450	945	995	600
SFS19444	19444	1840	5175	3315	3500	525	1390	1440	600
SFS22222	22222	1840	5525	3315	4000	600	1390	1440	600
SFS27777	27777	1840	5897	3315	5000	675	1390	1440	600
SFS33333	33333	1840	7045	3315	6000	900	1390	1440	2x600
SFS38888	38888	1840	8105	3315	7000	1050	1390	1440	2x600
SFS44444	44444	1840	939	3315	8000	1200	1390	1440	2x600
SFS50000	50000	1840	10695	3315	9000	1350	1390	1440	2x600
SFS55555	55555	1840	11804	3315	10000	1500	1390	1440	2x600

Additional Items
Mains Alarm (Mandatory)
Solar Alarm
Access Shaft mtr
Replacement Filter
Replacement Filter Wrap

Stephenson Road, Speedwell Industrial Estate, Staveley, Chesterfield, Derbyshire S43 3JN