MORCLEAN

Car Valeting Wash Bay Sump Separators (SS range)





Supplied with a D400 grating with a 600mm opening, wash water is contained within the separator tank to allow water to settle prior to connection to the mains foul drain.

The build-up of silt and dirt from vehicles is a major problem particularly from vehicle wash facilities and wash bay tank is designed to effectively trap the silt before it enters the foul drainage system.

The Wash Bay range is especially suited to hand car washing or smaller jet washing and valeting locations where there is a build-up of silt.

The Wash Bay Sump Separators are an extremely robust range of sumps that can be installed in a wash bay or car wash area. The range features two smaller silt traps at 275 litre (the SS1) and 450 litres (the SS2) silt retention and a larger 1000 litre unit namely the SS3.

All the units are supplied with a D400 Heavy Duty open grating for surface water catchment from vehicle wash bays.

For heavier washing or busier sites then we also have a range of 2 and 3 stage wash bay interceptors

Features & Design

- Designed in accordance to PPG13 & PPG3
- 250, 450 and 1000 litres models
- Supplied with removable D400 loading grating
- Super 'Heavy Duty' bodies
- Minimal granular surround installation
- Corrosion Free 50 year plus life expectancy
- Designed and manufactured totally in the UK



Tel: 01246 471147 Fax: 01246 471277

Stephenson Road, Speedwell Industrial Estate, Staveley, Chesterfield, S43 3JN, UK

sales@morclean.com www.morclean.com

