



Specifications

Туре	Mobile
Chemical	High pressure
Motor Specification	10hp, 1450rpm
Pressure	200bar / 3000psi
Product Weight	140kg
Power Supply	415v
Shutdown System	Auto stop/start
Size	21 Litres per minute
Temperature	0-150
Water	Hot
Water Flow	21 litres per minute

Standard Features

- Heavy duty steel chassis
- Stainless steel cover
- 4 large robust wheels for tough terrrain
- Large 31ltr easy fill fuel tank with low level sensor
- Efficient M2 boiler system & double spiral coil
- Steam stage with low pressure steam valve
- ST66 chemical valve for improved calibration
- Professional Interpump with ceramic pistons
- Industrial 1450rpm 4 pole electric Nicolini motor
- Automatic stop/start system
- Bypass valve and safety valve
- Pressure gauge
- Burner control with flow switch and thermostat
- 24v low tension safety controls
- Low level fuel warning lamp with a burner shut down
- Mains power on lamp
- Including 10mt high pressure hose, single lance and RL37 washgun with swivel

Morclean Ltd.

Tel: 01246 471147 Fax: 01246 471277 Stephenson Road, Speedwell Industrial Estate, Staveley, Chesterfield, S43 3JN, UK sales@morclean.com www.morclean.com

