

MAV 15-45 COMPRESSED AIR POWERED DRY VACUUM

This range of Industrial Vacuum Cleaners is available in Dry Pick Up only versions or Wet & Dry versions that can be converted to pick up either dry dust and debris or non-flammable liquids. All models are suitable for use in Gas Zone 1 and Dust Zone 21, have been fully earth bonded, and have an Anti-Static (conductive) vacuum hose and air supply hose. Every vacuum cleaner is individually tested and provided with its own test certificate for earth path continuity. *not suitable for dusts hazardous to health



FEATURES

- Easy to use
- Accessible for service
- Optimal suction power
- Robust chassis
- Drain hose
- Large rear wheels and rotating front wheels
- Storage for accessories and cables
- For dry only vacuum application.



Category 2 (Dust Zone 21 / Gas Zone 1)
 II 2 D Ex h IIC T50°C Db
 II 2 G Ex h IIC T6 Gb

TECHNICAL SPECIFICATIONS

Filtration:

1st Stage Disposable Microbre Bag | 2nd Stage Anti-Static (Conductive) Cloth Filter

Mobility

MAV 15 & MAV 20 - 4x75mm Conductive heavy Duty Castor | MAV 18, 30 & 45 - 2x75mm Conductive Heavy-Duty Castors & 2x200mm Conductive wheels on a Heavy Duty Tubular Stainless Steel Caddy (with detachable canister)

Model	Dimensions (mm) H x W x D	Weight (kg)
MAV 15	430 x 380 x 380	6.5
MAV 18	895 x 410 x 420	11.5
MAV 20	525 x 440 x 440	9.0
MAV 30	895 x 460 x 500	14.5
MAV 45	895 x 460 x 500	15.9

Cleaning range from Air Point:
 16 Metres/52 Feet

All models are supplied with a certificate of earth path continuity, a 5 metre conductive air supply hose, a 38mm conductive hose and toolkit. All models are also supplied with 5 disposable microbre bags.

Note: It is the end user's responsibility to ensure and maintain a good earth bond at the compressed air connection point. All Morclean Airvacs ATEX approved as category 2 II 2 D Ex h IIC T50°C Db / II 2 G Ex h IIC T6 Gb