

MV 20, 25, 30, 45 & 50 INDUSTRIAL WET AND DRY VACUUM CLEANERS

Built without compromise to offer years of reliable service, this versatile range of industrial wet and dry vacuum cleaners will happily take on the toughest jobs. There is a model in this range perfectly suited to your requirement, with the choice of dent proof injection moulded or non-magnetic stainless steel canister, 4 castor chassis or heavy duty tubular caddy, and a choice of single or double motors on all sizes of canister. The MV 50 features the extra advantage of pivoting tip action for emptying water into a drain or WC.



FEATURES

- Twin fan bypass cooling motor | One or two motors
- Thermal switch protection against overheating
- Virtually indestructible injection moulded plastic motor head
- Efficient float ball wet shut off
- Net filter to float cage to prevent motor damage
- Two stage dry filtration disposable paper bag & cloth filter
- Optional high efficiency cloth filter
- MV 30, 45 & 50 can be fitted with our bolt on fixed floor tool
- Hose entry will accept 32, 38 & 51mm hose and tool kits
- MV 30 & 45 can be fitted with dump valve or drain hose and stopper for quicker wet emptying
- Antistatic hose entry and 38mm conductive tool kit to dissipate build up of nuisance static.
- Available for models with stainless steel canister at time of order or as a retro fit.



38mm WD1 tool kit

Motor: Single Motor 1000w Max, 800w Mean | Twin Motor 2000w Max 1600w Mean Power: 230/110v - 50/60Hz Performance Single Motor - Max Airflow - 43.5Ltr/Sec | Twin Motor Max Airflow - 82Ltr/Sec Capacity Wet/Dry Litres: MV 20 14/20L | MV 25 18/23L | MV 30 24/30L | MV 45 34/40L | MV 50 34/40L Dimensions (H x W x D) mm: MV 20 610x440x440 | MV 25 625x440x440 | MV 30 865x450x460 | MV 45 865x450x460 | MV 50 920x520x560 Weight (Kg) Single/Twin: MV 20 3.5/16.25 | MV 25 12.5/15.25 | MV 30 16.8/19.7 | MV 45 17.8/20.7 | MV 50 19/22 Cleaning Range: 28.5 Metres / 94 Feet

TECHNICAL SPECIFICATIONS