

Standard Duty Floor

The Standard Duty Floor is carried out in Basic PVC and is the most sold variant.

This variant is optimally suited for use as a mobile washing station, since the BasicPVC is strong and robust, but still relatively light in weight. We have many customers with mobile truck washing businesses or transport companies who clean their fleet on location using a Basic PVC version Morclean mobile floor.

	Basic PVC		PVC coated polyesterfabric
1	Standard colour(s)		Light grey (code 7001), orange (code 3056), dark grey (code 7244)
2	Base Fabric (W/F)		Trade mark Polyester
3	Yam (W/ F)		1100/ 1100 dtex
4	Weave		P 2/2
5	Total weight	DIN EN ISO 2286-2 BS 3424 method 5B	Appr. 900 g/ sqm
6	Coating material		PVC
7	Tensile strength (W/F)	DIN 53 354 BS 3424 method 6A	4000/ 3500 N/ 5 cm
8	Tear resistance (W/F)	DIN 53 356 BS 3424 method 7A	600/ 600 N
9	Coating adhesion	DIN 53 357 BS 3424 method 9B	At least 90 N/ 5cm
10	Temperature resistance	DIN EN 1876-2 BS 3424 method 10	-30 / + 70 degrees Celcius
11	Lichtechtheid	DIN EN ISO 877 BS 3424 method 15	7-8
12	Liquid tightness	BS EN 20811	>400 cms/ H2O

W/F = Warp/weFt

Table - Standard Duty Floor