

# MORCLEAN

Let's Innovate

## e-series

### HSE1/2/3/4/5/6/7

#### ELECTRICALLY HEATED STATIC PRESSURE WASHER

- 80°C with market leading heat retention
- 375Ltr stainless steel lagged water tank
- High quality steel cabinet with all standard cabinet features
- Larger water tank and increased heating power gives a longer run time with constant heat
- Low revving 1450rpm pump & motor
- High temperature Interpump
- Unique stainless steel subframe construction
- Easy access for servicing
- Double insulated hot water tank
- Low thermal loss in standby
- Maximum temperature output 80°C
- Digital temperature display
- Simple 24v controls
- Available from 18-48kw heating power
- Lockable powder coated steel front door
- Hinged and removable cabinet front door and lid



**MADE IN GREAT BRITAIN** 

### TECHNICAL DATA

THE HSE 1-7 ARE DESIGNED TO RUN ON A STANDARD 32AMP POWER SUPPLY

PRODUCT CODE	HSE1	HSE2	HSE3	HSE4	HSE5	HSE6	HSE7
Water Flow	11Ltrs per minute	13Ltrs per min	13Ltrs per min	15Ltrs per min	13Ltrs per min	15Ltrs per min	18Ltrs per min
Pressure	120bar	170bar	170bar	200bar	170bar	200bar	160bar
Motor Specification	4hp,3Kw,1450rpm	7.5hp,3Kw,1450rpm	7.5hp,5.5Kw,1450rpm	7.5hp,5.5Kw,1450rpm	7.5hp,5.5Kw,1450rpm	7.5hp,5.5Kw,1450rpm	7.5hp,5.5Kw,1450rpm
Heating Power	18-12Kw	24Kw	36Kw	36Kw	48Kw	48Kw	48Kw
Volts / Amps / Watts	400v/32A/22Kw	400v/45A/29.5Kw	400v/63A/41.5Kw	400v/63A/41.5Kw	400v/80A/41.5Kw	400v/80A/41.5Kw	400v/63A/41.5Kw
Shutdown System	Timed total stop	Timed total stop	Timed total stop	Timed total stop	Timed total stop	Timed total stop	Timed total stop
Max Temperature	80°C	80°C	80°C	80°C	80°C	80°C	80°C
Weight	250kg	250kg	250kg	250kg	250kg	250kg	250kg
Dimensions (h x w x d)	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm